


QUICK DISCONNECTS

Fully Insulated Female Quick Disconnects



• Material

- Insulation: Vinyl
- Terminal Body: Brass
- Metallic Sleeve: Copper
- Plating: Tin



Fully Insulated Female Quick Disconnects

WIRE RANGE mm ² (A.W.G.)	TAB SIZE Thickness × Width	ITEM NO .	DIMENSION mm(inch)				COLOUR
			W	L	B	C	
0.5-1.5 (22-16)	0.5×2.8 .020×.110	WT8	3.2(.126)	19.0(.748)	10.5(.413)	1.7(.067)	RED
	0.8×2.8 .032×.110						
	0.5×4.75 .020×.187	WT9	5.0(.197)	20.5(.807)			
	0.8×4.75 .032×.187						
1.5-2.5 (16-14)	0.8×6.35 .032×.250	WT10	6.6(.260)	21.8(.858)	10.5(.413)	2.3(.091)	BLUE
	0.5×4.75 .020×.187	WT11	5.0(.197)	20.2(.796)			
	0.8×4.75 .032×.187						
4-6 (12-10)	0.8×6.35 .032×.250	WT12	6.6(.260)	22.2(.874)	12.5(.492)	3.4(.134)	YELLOW
	1.2×9.4 .047×.375	WT13	10.0(.394)	30.5(1.201)			

Materials

Conductor: Brass
 Sleeve: Copper tubular
 Insulation: Vinyl
 Plating: Tin

Operating temperature: -10°C to +75°C
 Max. voltage rating: 300V
 Max. current rating: Red - 10A, Blue - 15A, Yellow - 24A
 Flared barrel for easy wire insertion
 Low insertion force and easy crimping whilst ensuring secure termination